

# DUST SENTRY PRO

## Real-time multi-channel particle monitor for aerosol profiling

Designed for environmental professionals who need to monitor and manage multiple outdoor dust and particle size fractions, simultaneously and in real-time.

The Dust Sentry Pro delivers simultaneous measurement of PM<sub>10</sub>, PM<sub>2.5</sub>, PM<sub>1</sub>, TSP, and particulate counts for 8 different channels; 0.3, 0.5, 0.7, 1.0, 2.0, 3.0, 5.0, 10 microns.



### What is it?

- Reduce failure and downtime thanks to this robust purpose-built outdoor dust profiler
- Set up and deploy in under 10 minutes – get live data flowing to your PC or mobile
- Reduce site visits using two-way communications – remotely troubleshoot, upgrade software, change settings, and calibrate
- Plug in all your devices – noise, weather, reference monitors – to the Dust Sentry Pro power and data interface and view data in one software dashboard
- Power up with quick and easy interface to solar and battery systems
- Respond in real-time via configurable email / SMS alerts

### What can it measure?

- Multiple dust fractions, wind, weather and noise



### Who is it for?

- **Industrial operators** who need to manage multiple dust and particulate fractions from site activities within regulatory or permitted limits:
  - Construction and remediation projects
  - Quarry and mine operators
  - Port and bulk handling terminals
  - Waste management sites
- **Environmental consultants** who need to measure multi-channel PM size fractions without the usual time and hassle of air monitoring projects
- **Regulatory authorities** who need to fill the gaps in the regulatory PM monitoring network
- **EHS managers** who need to demonstrate that they are providing a safe environment for the people in their care
- **Researchers** who want simultaneous and accurate data across a range of particulate profiles

# Specifications | Dust Sentry Pro

Particle Module	Sizes	Range	Accuracy	Flow Rate	Lower Detectable Limit (2σ)
Profiler (Optical Particle Counter)	PM <sub>1</sub> , PM <sub>2.5</sub> , PM <sub>10</sub> AND TSP	PM <sub>1</sub> 200 µg/m <sup>3</sup> PM <sub>2.5</sub> 2000 µg/m <sup>3</sup> PM <sub>10</sub> 5000 µg/m <sup>3</sup> TSP 5000 µg/m <sup>3</sup>	<±(5 µg/m <sup>3</sup> + 15% of reading)	1.0 LPM	<1 µg/m <sup>3</sup>
Optional Particulate Counts	0.3, 0.5, 0.7, 1.0, 2.0, 3.0, 5.0, 10 microns	0-1000000 particles/L			
<b>System Specifications</b>					
Control System	Embedded fanless PC (Intel Celeron® N3350, 1.1GHz, dual core, 4GB RAM, 32GB SSD hard drive), Ubuntu Linux Operating System				
Communications <sup>1</sup>	Standard: WIFI, Ethernet (LAN) Optional modem: Cellular IP 3G HSPA or 4G LTE				
Software	<b>Aeroqual Cloud</b> – Choose a plan that is right for you <b>Optimize:</b> Reduce site visits and improve data quality by managing your monitors and optimizing network performance remotely. <b>Plus:</b> Stay one step ahead with enhanced features for viewing and sharing data, real-time alerts, and analysis. Talk to our sales team to learn more about Aeroqual Cloud plans.				
Data logging	32 GB Hard Drive (> 5 years data storage)				
Averaging period	1 min, 5 min, 10 min, 15 min, 20 min, 30 min, 1 hr, 2 hr, 4 hr, 8 hr, 12 hr, 24 hr				
Power requirements <sup>2</sup>	100-260 VAC (standard): 24.7 W, Regulated 12 VDC (if required): 27.2 W				
Enclosure	Lockable IP65 GRP cabinet with integrated aluminum solar shield armor				
PM Sampling System	Inlet: Omni-directional 36 cm (14.1 inches) heated inlet Pump: 12 V brushless DC diaphragm				
Dimensions <sup>3</sup>	483 H x 330 W x 187 D mm (19 H x 13 W x 7.4 D inches) Includes solar shield armor & mounting brackets				
Weight <sup>4</sup>	< 13 kg (28.6 lbs)				
Environmental operating range	-10 °C to +45 °C (14 °F to 113 °F)				
Mounting	Pole, tripod and wall mounting brackets included				
Factory integrated sensors <sup>5</sup>	Gill WindSonic (ultrasonic wind sensor), Vaisala WXT536 (weather transmitter), Met One MSO (weather transmitter), Cirrus MK427 Class 1 (noise sensor), Novalynx Pyranometer (solar radiation)				
Compatible tested sensors	BSWA 308 (sound level meter), Met-One BC-1060 (black carbon monitor), Met-One E-BAM PLUS (Beta-Attenuation Mass Monitor)				

<sup>1</sup> 4G LTE not available in all markets.

<sup>2,4</sup> Configuration used for power and weight calculations: base unit, nephelometer, PM<sub>10</sub> sharp cut, modem, heater on.

<sup>3</sup> Dimensions are for enclosure. PM sampling inlet with cyclone adds 360 mm (14.17") to total height.

<sup>5</sup> Optional

